
Secureye

DATASHEET

16+2 Long Distance

10/100 PoE Switch



SPECIFICATION	S-16FE-2UE-LD
PoE Port	1 to 16 port 10/100Mbps support IEEE802.3af/at
SFP Port	Supported
Output Power	15.4W/30W IEEE802.3af/at
Power Supply Method	Both 1/2+,3/6- and 4/5+, 7/8-
Whole Power	≤ 250W
POE Standard	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
POE Power Transmission Distance	≤ 250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100/1000Mpbs 5 class and above non shielded twisted pair
Network Signal Distance	≤ 250m
Switch Capability	7.2Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps 1001000Mbps:14800pps
MAC Address	MAC address table 8K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Environment	Working Temperature : -10°C ~ 60°C
Input Power	AC100-240V 50/60HZ
Weight	2.125kg
Size	270mm*180mm*44mm(L*W*H)

CE FC RoHS COMPLIANT

www.secureye.com