

32CH NVR



H.264
Compression



Supported Browser



www.secureeye.com

SPECIFICATION

S-32NV-4HD-5HN

Audio / Video	Video Input	32CH
	Video Output	HDMI(1920×1080/1440×900/1280×1024/1280×800/1024×768) VGA(1920×1080/1440×900/1280×1024/1280×800/1024×768)
	Audio Input	1CH RCA
	Audio Output	1CH RCA
	Video Compression	H.264
	Video Capacity	32CH 5MP/3MP/2MP/1.3MP/1MP
Storage	Audio Compression	G.711
	Interface & Capacity	4 SATA (Max.6TB/pcs)
	File Format	Log: *.txt/Picture: *.JPG/Video: *.mp4
	Maximum Log	2000
Recording	USB	USB flash disk/external HDD (FAT32)
	Type	(All/Scheduled/Auto/Alarm/Motion Date/IVP)
	HDD full	Overwrite/Stop recording
	Playback	4CH 2MP/4CH 3MP/3CH 4MP/2CH 5MP Last Hr./Next Hr.,Last Frame/Next Frame, Backward(8X 16X)
	Playback Control	Pause/PlaySlow(x1/2 x1/4 x1/8 x1/16)Fast Forward(x2 x4 x8 x16)
Network	Search Mode	By CH/Type/Date (Single or combined)
	Ethernet	10M/100M/1000M
	Max. Remote Channels	64CH
	Protocols Supported	TCP/IP,DHCP,UDP,SMTP,NTP
	Compatibility	ONVIF
Interface	Remote Connection	CMS Client/WebCC/ APP
	Network	1x RJ-45
	USB	1x USB2.0,1xUSB3.0
	PTZ	RS485
	Control Device	Mouse/Remote Control/Front Panel
Features	Remote Power Control	Power on/off
	Alarm Input	6CH(NC/NO)
	Alarm Output	1CH(Default NO)
	Screen Layout	(1/2/4/8/9/16/25/33)
	Alarm Actions	Buzzer/Send to Client/alarm email
	Magnification	Support
	USB Recovery	Support
	2Way Communication	Support
General	Privacy Mask	Support
	Video Lost Alarm	Support
	Snapshot on alarm	Support
	Working Temperature	-10°C ~ 55°C
	Working Humidity	10% ~ 90%
	Power Supply	DC12V
	Power Consumption	≤22W
	Language	Multi Languages
	Dimensions(W×H×D)mm	445*45*325
	Weight (g)	≤ 3300g