


8 Port 10/100/1000 PoE Switch



SPECIFICATION	S-8GE
PoE port	1 to 8 port support IEEE802.3af/at
UP link port	Null
SFP port	Un-support
PoE port output power	15.4W/30W IEEE802.3af/at
PoE power supply pins	Both 1/2+, 3/6-and 4/5+, 7/8-
Whole power	<150W
Protocol standard	IEEE 802.3af/IEEE 802.3at
PoE type	End-span
Transmission distance	100 ~ 150m
Network standard	IEEE 802.3, IEEE802.3u,802.3x,802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Network Signal Distance	<100m
Switch capability	16Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps / 1000Mbps:14800pps
MAC Address	MAC address table 8K
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	Each port occupied 1 LINK/ACT.1000Mbps, POE Status Indicator, Whole power indicator
Working Temperature	-10° ~ 55° C
Input power	AC110-240V 50/60HZ
Weight	1.8kg
Size	270mm*180mm*44mm(L*W*H)

