

FACE & PALM VEIN ACCESS CONTROL DEVICE



S-B120CB

Features:

- High-performance processor, responsive
- TFT color LCD screen
- Multi-factor authentication
- Infrared camera, can also quickly identify dim environments
- USB flash drive exports attendance reports
- UPS Battery Backup

Specification

Hardware Features	Camera	Color + infrared dual camera binocular 300,000 pixels
	Infrared Light	In the tank
	Display	1.77 inches
	Keyboard	Push button input
	Memory	64MB
	Storage	128MB
	Communication Interface	USB, Wiegand, RS485
	False Acceptance Rate	≤0.0001%
	USB Flash Drive Interface	Yes
	Speech Output	Yes
	Clock RTC	Exterior
	Operating Voltage	DC 12V±5%
	Ambient Light	0-8000Lux
	Access Control Port	Relay, Wiegand Output/Input
	Operating Temperature	0°C~45°C
	Operating Humidity	0%~80% non-condensing
	Product Dimensions	86mm×86mm×23.5mm
	Net Weight	106g
Gross Weight	140g	
Software Features	User Capacity	3000
	Face Capacity	3000
	Card Capacity	3000
	Palm Print Capacity	1000
	Password Capacity	3000
	Record Capacity	200000
	Department	16
	Shift	24
	Bell	24
	Verification Method	Face, Palm vein, Password, Card
	How To Confirm	FC/PP/P, P+FC/PP
	Supported Languages	English
	Self-test Function	Manual detection
	Power Management Features	Screen saver feature
	Face/verification Speed	≤0.6s
Face FAR/FRR	0.00001/0.1%	
Face Recognition Mode	1: N	
Palmar Vein Verifies Speed	≤0.6s	
Palmar Vein FAR/FRR	0.00001/0.1%	
Palmar Vein Recognition Pattern	1: N	

