

1 Door/2 Reader Network IP Controller



KEY FEATURES

- ▶ **Card Holder: 10,000 Cards**
- ▶ **Logs: 60,000 Records**
- ▶ **Alarm Events: 10,000 Events**
- ▶ **Communication: TCP/IP**



Features

S-IP1D2R

- Directly integrate 10M TCP/IP communication with excellent transmission performance.
- Flash memory card with big capacity can keep data for 10 years if the electricity goes off.
- Hardware has web server function, management and real time monitor can be realized without installing software.
- Support card readers to realize going in and out by swiping card.
- Time Zone: 4/8 & each group can choose different verification methods.
- Support multi verifications: Card, card+password, double cards, first card opening, timing door force open or close, & timing alarm
- Support remote operation of door & alarm, fire alarm opening or closing.
- Support door locking through software or WEB.
- Support anti-pass back going beyond access controllers.
- Support alarm output of multi events like invalid card & time, door alarm & door open overtime.
- Wiegand interfaces are compatible with wiegand 26/34 protocol.
- Automatic data sending & transporting is not influenced by quality of controllers.
- Support the setting of every card's valid time.
- Support real time management monitor by multi users & multi devices.
- Network real-time monitor can be realized working with web map.

Standard Interface

- Card Reader: 2pc
- Alarm Output: 1
- Alarm Input: 1
- Fire Alarm Output: 1
- Fire Alarm Input: 1
- Release Button: 1
- Door Sensor: 1
- Lock Output: 1

Basic Parameters

- Box Color: Black
- Working Temperature: -10C⁰ ~ +60C⁰
- Environment Humidity: 10% - 95% R.H
- Working Voltage: 12V
- Working Current: <150ma
- Rated Power: ≤ 10W
- Power-Off Protection: 10 Years

