

16ch XVR



SPECIFICATION		S-16C2H-2M
Video/Audio Input	Video Input	16-ch,BNC interface (1.0Vp-p, 75 Ω)connection,support UTC
	Supported camera types	Support AHD input:5MP 12.5fps, 4 MP 15fps, 3 MP 15fps, 1080p 25fps, 1080p 30fps, 720p 25fps, 720p 30fps Support TVI input:1080p 25fps, 1080p 30fps, 720p 25fps, 720p 30fps Support CVI input:1080p 25fps, 1080p 30fps, 720p 25fps, 720p 30fps Support CVBS input
Video/Audio output	Audio Input	16-ch, 2*DB15(need to connect DB15 to RCA line)
	CVBS Output	1-ch,BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480
	VGA Output	1-ch,1920X1080/1280X1024/1440X900/1024X768
	HDMI Output	1-ch,3840*2160/1920X1080/1280X1024/1440X900/1024X768
	Audio Output	1ch,RCA or HDMI output
Coding parameter	Video Compression	H.265
	Video Resolution	H5MP/H4MP/H1080P/720P/960H
	Video Frame Rate	1fps-25fps
	Video Bit Rate	128Kbps-5120Kbps
	Stream Type	Video / Video&Audio
	Sub-stream	CIF/15fps
	Audio compression	G711
	Audio Bit Rate	64kbps
Network management	Remote connections	Maximum connection: 15
	Network protocols	TCP/IP,HTTP,NTP,SMTP,ONVIF,P2P
Playback management	Recording mode	Timed recording/manual recording/motion recording
	Playback mode	Video file: Timeline mode playback; Capture file: File playback
Hard Disk Driver	Backup mode	Regular backup; edit backup
	Interface Type	2*3.5 inch SATA Interfaces
External Interface	Voice intercom	Support
	Network Interface	1*RJ45, 10M / 100M self-adaptive Ethernet interface
	USB Interface	2 *USB 2.0
	Power type	Φ5.5 round power interface
General	Power Supply	DC12V 4A
	Consumption	≤ 20W(without hard disks)
	Working Temperature	-10°C to +55°C (14°F to 131°F)
	Working Humidity	10% to 90%
	Dimensions	325*220*52mm
	Weight	≤ 2.5 kg

