

16 GE + 2 SFP Port PoE Switch



SPECIFICATION	S-16GE-2UG-250W
PoE port	16 10/100/1000 port support IEEE802.3af/at
SFP port	Yes
PoE port output power	15.4W/30W IEEE802.3af/at
PoE power supply pins	Both ½+, 3/6- and 4/5+, 7/8-
Transmission Distance	100 ~ 150m
Protocol standard	IEEE 802.3af/IEEE 802.3at
PoE type	End-span
Network standard	IEEE 802.3, IEEE802.3u,802.3x,802.3af/at
Network Medium	10/100/1000Mbps 5 class and above non shielded twisted pair
Network Signal Distance	<150m
Switch capability	7.2Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps / 1000Mbps:14800pps
MAC Address	MAC address table 8K
	Power priority mechanism, fast and forward, MAC automatic learning and aging
Port function	IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	Each port occupied 1 LINK/ACT,100Mbps, POE Status Indicator, Whole power indicator
Working Temperature	-10° ~ 55° C
Input power	AC100-240V 50/60HZ
Whole power	250W
Weight	4.125kg
Size	270mm*180mm*44mm(L*W*H)

