

# 16CH NVR



**H.264**  
Compression



*Supported Browser*



[www.secureeye.com](http://www.secureeye.com)

## SPECIFICATION

## S-16NV-2HD-5HN

|               |                      |   |
|---------------|----------------------|---|
| Audio / Video | Video Input          | 16CH  |
|               | Video Output         | HDMI(1920×1080/1440×900/1280×1024/1280×800/1024×768)<br>VGA(1920×1080/1440×900/1280×1024/1280×800/1024×768)<br>CVBS(1920×1080/1440×900/1280×1024/1280×800/1024×768) |
|               | Audio Input          | Support   |
|               | Audio Output         | Support   |
|               | Video Compression    | H.264   |
|               | Video Capacity       | 16CH 5MP/3MP/2MP/1.3MP/1MP  |
| Storage       | Audio Compression    | G.711U  |
|               | Interface & Capacity | 2 SATA (Max.6TB/pcs )   |
|               | File Format          | Log: *.txt/Picture: *.JPG/Video: *.mp4  |
|               | Maximum Log          | 2000  |
| Recording     | USB                  | USB flash disk/external HDD (FAT32)   |
|               | Type                 | Manual/Scheduled/Motion/Alarm   |
|               | HDD full             | Overwrite/Stop recording  |
|               | Playback             | 4CH 2MP/3CH 3MP/3CH 4MP/2CH 5MP   |
|               | Playback Control     | Last Hr./Next Hr.,Last Frame/Next Frame, Backward(8x16X)<br>Pause/PlaySlow(x1/2 x1/4 x1/8 x1/16), Fast Forward(x2 x4 x8 x16)  |
|               | Search Mode          | By CH/Type/Date (Single or combined)  |
| Network       | Ethernet             | 10M/100M/1000M  |
|               | Max. Remote Channels | 32CH  |
|               | Protocols Supported  | TCP/IP, DHCP, UDP, SMTP, NTP  |
|               | Compatibility        | ONVIF   |
|               | Remote Connection    | CMS Client/WebCC/APP  |
| Interface     | DDNS                 | Support   |
|               | Network              | 1x RJ-45  |
|               | USB                  | 1x USB2.0   |
|               | PTZ                  | RS485   |
| Features      | Control Device       | Mouse   |
|               | Screen Layout        | 1/2/4/8/9/16  |
|               | Alarm Actions        | Buzzer/Send to Client/alarm email   |
|               | Magnification        | Support   |
|               | USB Recovery         | Support   |
|               | Privacy Mask         | Support   |
|               | Video Lost Alarm     | Support   |
| General       | Snapshot on alarm    | Support   |
|               | Working Temperature  | -10°C ~ 50°C  |
|               | Working Humidity     | 10% ~ 90%   |
|               | Power Supply         | DC12V   |
|               | Power Consumption    | ≤ 15W (Without HDD)   |
|               | Language             | Multi Languages   |
| General       | Dimensions(W×H×D)mm  | 295*45*235  |
|               | Weight (g)           | 1130  |