

8+2 Port Long Distance 10/100 PoE Switch



SPECIFICATION	S-8FE-2UE-LD
PoE Port	1 to 8 port support IEEE802.3af/at
UP link port	2 UP LINK port
EXTEND	Can be changed to EXTEND, extend network cable up to 250m
PoE output	15.4W/30W IEEE802.3af/at
PoE pins	1/2+,3/6 - 4/5+,7/8- total 8 pins
PoE whole power	<150W
PoE connection	IEEE 802.3af/IEEE 802.3at
PoE type	End-span
POE transmission distance	<250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x,802.3af/at
Network Medium	10/100BASE-TX: 5 class and above non shielded twisted pair
Network Signal Distance	<250m
Switch capability	1.6 Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port / 100BASE-tx:14800pps/port
MAC Address	1K MAC address table
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	Each port with 1 LINK/ACT. 100Mbps. EXTEND switch indicator. POE Status indicator. POWER indicator
Working Environment	Working Temperature: -10°~ - 60°C
Input power	AC100-240V 50/60HZ
Whole power	Max.150W
Weight	1.7kg
Size	270mm*180mm*44mm(L*W*H)

