


36x High Speed Dome

Camera



Supported Browser



www.secureeye.com

KEY FEATURES

- 1.3 & 2MP Resolution
- 36x Optical Zoom
- 0 Lux/F1.4 Min. Illumination
- 256 Preset Position
- 150m IR Distance
- 8 Tour, 16 Preset position
- Plastic Body Construction

SPECIFICATION		S-HSD-1AHD-36XP S-HSD-2AHD-36XP	
Camera	Sensor	1/2.8" HD CMOS Sensor	
	Lens	5 ~ 120mm	
	Optical Zoom	36x	
	Image Resolution	1280x960	1920x1080
	Minimum Illumination	Color: 0.002LUX / F1.5, 0 LUX / F1.4 (IR ON)	
	Auto Day Night	On/Off	
	IR Range	150m	
	Exposure Mode	Auto/Shutter/Manual/IRIS/Bright	
System	Preset Position	256	
	Tour scan	8 tour, 16 preset position per tour, speed and dwell time, adjustable	
	Pattern Scan	4 pattern, 3 minutes recording for each pattern	
	Motion Detection	Yes	
	S/N Ratio	>50dB	
General	Shutter Speed	PAL: 1/50s -1/100,000s NTSC: 1/60s -1/100,000s	
	P/T/Z Control	Built-in RS485 P/T/Z control	
	Rotation Angle	Horizontal: 0° ~ 360°, Vertical: 0° ~ 90°	
	Rotation Speed	Horizontal: 1200 /s Vertical: 1200 /s	
	AGC	Auto / Manual	
	3D DNR	Supported	
	BLC	Auto / Manual	
	Digital Zoom	16X	
	WDR	120dB	
	Operating Temperature	-10°C ~ 50°C	
Power	DC12V 4A		
Housing	Plastic body construction		