



2 & 4 Megapixel H.265 Motorized

Network Bullet IR Camera



S-W2SIP-35M / S-W4SIP-35M



















Key Features

- 0.008Lux Starlight
- Super WDR up to 120dB
- H.265 High Efficiency Video Coding
- Integrated Motorized Variforcal Lens(Auto Focus)
- Built-in ICR Filter for Day/Night switching
- Built-in web server for IE/Firefox/Chrome/Sarari preview
- 3D-DNR, Privacy Masking and Motion Detection
- Micro SD/SDHC/SDXC card local storage support
- Built-in efficient IR LEDs, IR distance up to 35m
- Weather-proof IP67-rated Housing
- Built-in 802.3af Compliant PoE
- Support ONVIF Profile S

Supported Browser











Dimension (mm)







IP Video Surveillance Solution

Specification		S-W2SIP-35M	S-W4SIP-35M
	Image Sensor	ge Sensor 1/3" Progressive Scan CMOS	
Camera	Min. Illumination	Color: 0.008Lux @F1.2, B/W: 0Lux with IR on	
	WDR	Super WDR up to 120dB	
	Lens	Motorized 2.8 ~ 12mm	
	Field of View	H78.4°~H26.2°(2.8~12mm)	
	Shutter Time	1/100000s~1/5s	
	IR Distance	Up to 35m	
	Day&Night	ICR Filter Auto Switch	
Video	Max Image Resolution	1920*1080	2592*1520
		25fps(1920×1080),	20fps(2592×1520),
		25fps(1280×960),	25fps(2304×1296),
	Frame Rate	25fps(1280×720),	25fps(1920×1080),
		25fps(704×576)	25fps(1280×960),
			25fps(1280×720),
			25fps(704×576)
	Video Compression	H.265(HEVC)/H.264/MJPEG	
	Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	
	Image Setting	Brightness/Contrast/Saturation/Sharpness	
Network	Ethernet	1*RJ45 10M/100M Ethernet Port	
	Network Storage	NAS(Support NFS, SMB/CIFS)	
	Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS,	
		DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, IPv6, PPPoE, VLAN	
System	Storage	Support Micro SD/SDHC/SDXC, up to 64G	
	Advanced Function	Motion Detection, Privacy Masking, Backlight Compensation, 3D-DNR, ROI	
	SIP/VoIP Support	Yes, Voice & Video-over-IP	
	Event Trigger	Motion Detection, Network Disconnection, etc.	
	Event Action	FTP Upload/ SMTP Upload/ SD Card Record/SIP Phone	
	System Compatibility	ONVIF Profile S	
General	Power Supply	PoE/ DC12V±10%	
	Power Consumption	5.5W MAX, 9.5W MAX (With IR on)	
	Weather Proof	Up to IP67 Rating for Weather-resistant	
	Weight	820g	













