

# 2MP DOME IR CAMERA



## FEATURES

- Up to 1920 x 1080 high resolution
- 1/2.7" Progressive scan CMOS
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 3.6mm Megapixel Lens/M12
- 14μX18pcs SMD LED/ IR range up to 30M
- Support Smart IR
- Support Smart Functions
- Support Defog,ROI,UPnP-TM
- Support Tripple stream



[www.secureeye.com](http://www.secureeye.com)

SPECIFICATION		SIP-2HD-DIRE / S-IP-D1
Camera	Image Sensor	1/2.7" Progressive scan CMOS
	Min. Illumination	0.01lux(Color), 0lux(IR on)
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Lens	3.6 mm@F2.0: horizontal FOV: 88°, vertical FOV:47°
	Lens Mount	M12
	Day/Night	IR cut filter with auto switch
	Wide Dynamic Range	DWDR
	Max. IR LEDs Length	30M
	Smart IR	Support
	Compression	Video Compression
H.264 Codec profile		Base/Main/High profile
H.265 Codec profile		Main profile
Video Bit Rate		11 Kbps~8 Mbps
Image	Max.resolution	1920 × 1080
	Main Stream	50Hz:25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 25fps 720P(1280 × 720) 60Hz:30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960), 30fps 720P(1280 × 720)
	Sub Stream	50Hz:25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480), 30fps CIF(352 × 240)
	Mobile Stream	50Hz:25fps CIF(352 × 288) 60Hz:30fps CIF(352 × 240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	BLC	Support
	HLC	Support
	ROI	Support
	Defog	Support
	Network	Event
Smart Functions		Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving
Protocols		TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP, RTSP,RTCP,NTP,IGMP,UPnP,SMTP,SNMP,UPnP-TM,P2P,Bonjour
System compatibility		Onvif 2.6,Profile S, CGI
Security		User authentication,IP address filtering,Video mask
Mobile Surveillance		iPhone, iPad,Android devices
Communication interface		1 RJ45 10M / 100M Ethernet Port
General	Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE Supply	PoE (802.3af)(external POE)
	Power Consumption	Max. 5.5W
	Weather Proof	Indoor use only