

2MP BULLET IR CAMERA



FEATURES

- Up to 1920 x 1080 high resolution
- 1/2.7" Progressive scan CMOS
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 3.6mm Megapixel Lens/M12
- 14μX18pcs SMD LED/ IR range up to 30M
- Support Smart IR
- Support Smart Functions
- Support Defog, ROI, BLC, HLC, UPnP-TM
- Support Tripple stream
- NAS Supported



www.secureeye.com

SPECIFICATION		SIP-2HD-W20E / S-IP-W1
Camera	Image Sensor	1/2.7" Progressive scan CMOS
	Min. Illumination	0.01lux(Color), 0lux(IR on)
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Lens	3.6 mm@F2.0: horizontal FOV: 88°, vertical FOV:47°
	Lens Mount	M12
	Day/Night	IR cut filter with auto switch
	Wide Dynamic Range	DWDR
	Max. IR LEDs Length	30M
	Smart IR	Support
	Compression	Video Compression
H.264 Codec profile		Base/Main/High profile
H.265 Codec profile		Main profile
Video Bit Rate		11 Kbps~8 Mbps
Image	Max.resolution	1920 × 1080
	Main Stream	50Hz:25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960),25fps 720P(1280 × 720) 60Hz:30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)
	Sub Stream	50Hz:25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)
	Mobile Stream	50Hz:25fps CIF(352 × 288)60Hz:30fps CIF(352 × 240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	BLC	Support
	HLC	Support
	ROI	Support
	Defog	Support
	Event	Motion Detection, Video Shelter
Smart Functions	Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving	
Network	Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP, NTP,IGMP,UPnP,SMTP,SNMP,UPnP-TM,P2P,Bonjour
	System compatibility	Onvif 2.6,Profile S, CGI
	Security	User authentication,IP address filtering,Video mask
	Mobile Surveillance	iPhone, iPad,Android devices
General	Communication interface	1 RJ45 10M / 100M Ethernet Port
	Operating Conditions:	-30 °C ~ 60 °C (-22 °F ~ 140 °F)Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE Supply	PoE (802.3af)
	Power Consumption	Max. 5.5W
	Weather Proof	IP66