

High Performance Speed Door



KEY FEATURES

- External & Internal application and compact design.
- Safe and Secured for continuous operations.
- Self-supporting construction with anti-crash protection system.
- Smooth and fastest opening and closing.
- Protects traction unit, enables rapid wiring and safety photocell.
- Flexible curtain in self-extinguishing material.
- Modular interchangeable panels permit to replace worn or damaged panels.
- Vertical seals made of friction - resistant semi-hard PVC.
- Advance and robust control device.

SPECIFICATION		SC-S-HSD
High Performance Speed Door	Opening Speed	Up to 0.8 m/s
	Closing Speed	0.8 m/s
	Wind Load Class	Class 1 & Class 2
	Water Permeability	Class 3
	Power supply	230 V, 14Amp, 50-60Hz
	Motor	WITH BRAKE POWER 0.75 KW
	Advised operating temperature	-5°C up to +40°C
	Motor IP RATING	IP55
	Control Box	FMPL-400
	Design	Compact
	Drum	GI
	Motor Placed	Outside the drum
	Curtain Thickness	0.8 - 1.3 mm
	Motor Cover	GI
	Bottom Safety Edge	Aluminium with soft Rubber/EPDM
	Wind Bar	Yes (Aluminium)
	Side Guide Size	80 X 90 X 2 mm
	Vision Panel thickness	2.0 mm
	Top Cover	GI
	Side Cover	GI
Max. Dimension	(W) 6000X(H) 6000 mm	

