

*With*  
**AI & VLAN  
FUNCTION**



## 8Giga + 2SFP L2 MANAGED POE SWITCH

SPECIFICATION	S-8GE-M-2UG-AI-VLAN
Network standard	IEEE 802.3i IEEE 802.3u IEEE 802.3x IEEE802.3z, IEEE 802.3ab IEEE 802.3af IEEE 802.3at
Port	8 10/100/1000Mbps RJ45 port, 2 gigabit SFP fiber port, 1 Console port
Poe	8 10/100/1000Mbps RJ45 port support PoE+ power, Total max 150W, Single port max 30W
Indicator	10 Link/Act LED indicator, 8 POE LED indicator, 1 Power LED indicator, 1 SYS LED indicator
Performance	Forwarding mode store-and-forward, Bandwidth: 20Gbps, Packet forwarding rate: 14.88Mpps, Support 8K MAC address table
Shortcut function	One key AI VLAN, One key AI Extend(1-8 port 250meters PoE distance) One key AI PoE, One key QoS (Video priority)
Input power	100-240V/50-60Hz
Environmental	Operating temperature: 0°~40°C, Storage Temperature: -40~70°C, Operating Humidity:10%~ 90%, non-condensing, Storage Humidity : 5%~ 95%, non-condensing

