

IP BULLET IR Camera *With* SD Card Support



Features:

- 3.6mm Lens
- 14mil x 18pcs SMD LED
- 30m IR Range
- H.264/H.265 Compression
- Smart Analytics
- Onboard Storage: Built-in Micro SD/SDHC/SDXC slot, supports up to 128GB



Specification		S-IP-W5
Camera	Sensor+DSP	IMX335+Hi3516EV300
	Sensor	1/2.8" Progressive scan CMOS Sensor
	Min. Illumination	0.01lux(Color), 0lux(IR on)
	Lens	3.6 mm@F2.0: horizontal FOV: 85°, vertical FOV:44°
	Lens Mount	M12
	IR	14mil x 18pcs SMD LED
	IR Range	30m
	Smart IR	Support
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Day/Night	IR cut filter with auto switch
	Wide Dynamic Range	DWDR
	Digital noise reduction	2D/3D DNR
Compression	Video Compression	H.264/H.265
	H.264 Codec profile	Base/Main/High profile
	H.265 Codec profile	Main profile
	Video Bit Rate	11 Kbps~10 Mbps
Image	Max. Image Resolution	5MP(2592 × 1944)(default 15fps)
	Frame Rate	50Hz: 15fps 5MP(2592×1944), 15fps 4MP(2560×1440), 15fps 4MP(2304×1728), 25fps 3MP(2048×1536), 25fps 1080P(1920×1080), 25fps 960P(1280×960), 60Hz: 15fps 5MP(2592×1944), 15fps 4MP(2560×1440), 15fps 4MP(2304×1728, 30fps 3MP(2048×1536), 30fps 1080P(1920×1080), 30fps 960P(1280×960) 30fps 720P(1280×720)
	Sub Stream	50Hz:25fps 720P(1280×720), 25fps D1(704×576), 25fps CIF(352×288) 60Hz:30fps 720P(1280×720), 30fps D1(704×480), 30fps CIF(352×240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	BLC	Support
	HLC	Support
	ROI	Support
	Defog	Support
Network	Protocols	TCP/IP, ICMP, HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPV6
	Event	Motion Detection, Video Shelter
	Smart Functions	Line Crossing,Area Intrusion,Region Entrance,Region Exiting, Fast Moving, Face Detection
	System compatibility	Onvif(Profile S), CGI
	Security	User authentication,IP address filtering,Video mask
	Mobile Surveillance	iPhone, iPad, Android, CMS, WEB
General	Communication	1 RJ45 10M / 100M/ Ethernet Port
	On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128GB
	Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE Supply	PoE (802.3af)
	Power Consumption	MAX. 8.5W
Weather Proof	IP66	