

# HD-IP IR HIGH SPEED DOME CAMERA

With  
**Starlight**  
TECHNOLOGY



**Lightning Protection**



**Support P2P function**




**IP 66 Rated**



**IR Distance  
Up to 150 Meters**



**OnVif Compliant**



**POE**

**Features:**

- Support P2P function
- 7" Body Construction, IP66
- Optional function: POE, TF Card Slot
- ONVIF Compliant
- Intelligent IR illumination & power Consumption is Variable dependant the zoom factor

**2MP**  
RESOLUTION



**PAN / TILT**



**AUTO FLIP**

**Specification**

**S-PTZ-D2IP-20X-150M**

Solution	1/2.8" 2.0MP CMOS Hi3516E+Sony307
Output Pixel	1920x1080@20fps / 1920x1080@25fps
Lens	20X, F=4.7-96.3mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR,3DNR
WDR	DWDR
S/N Ratio	≥50dB
Auto Control IR LED	PWM
LEDs	6PCS IR LEDs+2PCS Laser LEDs
IR distance	Up to 150M
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Video Compression	H.265/H.264/M-JPEG
Software Control	IE, CMS, Management Platform, P2P
Rotation range	Pan:0~360°, Tilt:0~93°
Rotation speed	Pan:0~80°/s , Tilt:0~40°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmable (scan speed 1-64 levels setting available)
Guard Tours	3 groups( Max.16 points, dwell time user selectable)
Operating temperature	-40°C~+60°C
Power	DC 12V 4A / PoE(802.3at)
Consumption	≤25W
Lightning Protection	Transient voltage 6000V
Related Validation	IP66, CE, FCC, RoHs

