

HD-IP IR HIGH SPEED DOME CAMERA

With
Starlight
TECHNOLOGY



IR Distance
Up to 120 Meters



Lightning Protection



Support P2P function



OnVif Compliant



Video Compression



Power

Features:

- 7" Body construction, IP66
- Support P2P function, H.265
- ONVIF compliant
- Intelligent IR illumination & power consumption is variable, dependant the zoom factor



RESOLUTION



PAN / TILT



AUTO FLIP

Specification

S-PTZ-D2IP-36X-120M

Sensor	1/2.8" 2MP CMOS Hi3516A+Sony327
Output pixel	1920*1080p@30fps / 1920*1080p@25fps
Lens	36X f=4.6~ 167mm
BLC	Support
AGC	Auto/Manual
WB	Indoor/Outdoor/Auto/Manual
DNR	2DNR,3DNR
WDR	DWDR
S/N Ratio	≥50dB
Auto Control IR LED	PWM
IR distance	Up to 120 meters
LEDs	8Pcs IR LED
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Software Control	IE, CMS, Management Platform, P2P
Mobile View(optional)	Android, iPhone
Rotation range	Pan:0~360°, Tilt:0~93°
Rotation speed	Pan:0~200°/s, Tilt:0~100°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets(dwll time 01-60s interval available)
A-B scan	User programmable (scan speed 1-64 levels setting available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
Video compression	H.265/H.264/M-JPEG
Operating temperature	-40°C~+60°C
Power	DC 12V 4A
Consumption	≤25W
Related validation	IP66,CE,FCC,RoHS
Lightning Protection	Transient voltage 6000V

