

HD-IP IR HIGH SPEED DOME CAMERA

With
Starlight
TECHNOLOGY



IR Distance
Up to 280 Meters



Support P2P
Function



Lightning
Protection



Audio Compression



Video Compression



Power



Pan - Tilt



Auto Flip



Onvif Compliant

Features:

- Support P2P function
- 10" Full Metal Body Construction, Ip66
- 10PCS IR LED + 5PCS Laser LED
- IR range up to 280M
- Optional function: Audio (1In, 1Out), TF Card Slot
- ONVIF Compliant
- Intelligent IR illumination & power consumption is variable, dependant the zoom factor

SPECIFICATION	S-PTZ-D2IP-36X-250M	S-PTZ-D5IP-36X-250M
Sensor	1/2.8" CMOS 2MP Hi3516A+Sony327	1/2.8" CMOS 5MP Hi3516A+Sony335
Output pixel	1920*1080p@30fps / 1920*1080p@25fps	2592x1944@25fps / 2592x1520@30fps
Lens	36X f=4.6mm -167mm	
BLC	Support	
AGC	Auto/Manual	
WB	Indoor/Outdoor/Auto/Manual	
DNR	DNR,3DNR	
WDR	DWDR	
S/N Ratio	≥50dB	
IR distance	Up to 280 meters	
LEDs	10PCS IR LED + 5PCS Laser LED	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P	
Software Control	IE, CMS, Management Platform, P2P	
Mobile View(optional)	Android , iPhone	
Rotation range	Pan:0~360°,Tilt:0~93°	
Rotation speed	Pan:0~200°/s, Tilt:0~100°/s	
Auto Flip	Horizontal 180°,Vertical 93°	
Preset Points	220pcs presets (dwell time 01-60s interval available)	
A-B scan	User programmable (scan speed 1-64 levels setting available)	
Guard Tours	3 groups(Max.16 points, dwell time user selectable)	
Video compression	H.265/H.264/M-JPEG	
Audio compression	G711, PCM	
Lightning Protection	Transient voltage 6000V	
Operating temperature	-40°C ~ +60°C	
Power	DC 12V 5A	
Consumption	≤25W	
Related validation	IP66, CE, FCC, RoHs	

