

HD-IP PTZ DOME VANDALPROOF CAMERA



With
Starlight
TECHNOLOGY



Mobile
View



IR Distance up to
45 Meters

H.265

Compression
Supported

P2P

Support P2P
Function



POE

Features:

- 1.5 inch Vandal proof body, IP67.IK10
- IR range reach up to 45 Meters
- Pan/Tilt/Zoom, A-B scan, tour available
- Support Onvif; Support P2P function
- Support Audio, POE
- Support H.265/H.264 compression

SPECIFICATION

S-PTZ-D2IP-4X-45M

Sensor	1/2.8" 2.0MP Hi3516E+Sony307
Output pixel	1920x1080@25fps/1920x1080@20fps
Lens	4X=2.8-12mm
D/N	IR-CUT
BLC	Auto
WB	Auto
S/N Ratio	>50dB
Communications Protocol	TCP/IP,HTTP,NTP,IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
Video compression	H.265, H.264
Software Control	IE, CMS, Management Platform
Audio compression	G711, PCM
Mobile View	Android, iPhone
Pan Range	0°-350°
Tilt Range	0-70°
Pan Speed	0-25°/s
Tilt speed	0-20°/s
Preset Points	220
Guard Tours	3 groups (each group 16 preset, dwell time and speed selectable)
AB scan range	Any point in range: 0°~70° and 0°-355°
AB scan speed	1-9 grades
Operating Temp.	Outdoor: -30°C~+60°C
Auto Control IR LED	PWM
LEDs	4PCS IR LEDs
IR distance	Up to 45 meters
Power Supply	DC12V 2A(Not included) / PoE(802.3at)
Humidity	≤95% Non Condensing
Consumption	≤10W
Certification	IP66, CE, FCC, RoHs

