











# 4G Outdoor WIFI CAMERA



 <b>AUDIO</b>	 <b>WiFi</b>
 <b>MOTION</b>	 <b>4G</b>
 <b>SMART H.264 COMPRESSION</b>	 <b>DUAL STREAM</b>
 <b>MOBILE</b>	 <b>P2P</b>
 <b>CLOUD TECHNOLOGY</b>	 <b>TF CARD</b>

SPECIFICATION	SIP-2HDG-W40
Image Sensor	Sony STARVIS 2MP 1/2.8 IMX307 CMOS
Minimum Illumination	0.001Lux @(F1.4,AGC ON) ,0 Lux with IR
Shutter	Self-adaptive shutter
Lens	3.6mm,M12
Day & Night	IR cut filter
Infrared distance	30 Meters
Video Compression	Smart H.264
Video Compression Standards	Main Profile
Video Bit Rate	Adaptive bit rate
Audio Compression Standards	AAC
Audio Compression Rate	Adaptive Bit-rate
Max. Resolution	HD:1920X1080 SD:640x360
FPS	15fps, Network transmission frame rate adaptation
Image setting	Mirror, flip
Intelligent alarming	Input: Humanoid detection Output: Linked custom audio, linked lighting
Configuration	SmartConfig, AP configuration, Manually
Port agreement	Cloud privacy agreement
General function	Anti flicke, double stream, mirror, password protection, watermark
Storage interface	Micro SD card(maximum128G)
Power interface	Φ5.5 round head power interface
Wireless standard	IEEE802.11b, 802.11g, 802.11n
Frequency	2.4 GHz ~ 2.4835 GHz
Channel bandwidth	Support 20MHz
Safety	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission rate	11b:11Mbps, 11g:54mbps, 11n:150mbps
Network	FDD-LTE,TDD-LTE,WCDMA/HSPA+,TD-SCDMA,GSM/GPRS/EDGE
Frequency band	LTE-B1/B3/B8/B38/B39/B40/B41; WCDMA-2100/900Mhz; TD-SCDMA-B34/B39; GSM/GPRS/EDGE-900/1800Mhz
Transmission Rate	FDD-LTE: Uplink50Mbps / downlink150Mbps TDD-LTE: Uplink50Mbps / downlink150Mbps HSPA+: Uplink5.76Mbps / downlink21Mbps TD-SCDMA: Uplink5.76Mbps / downlink2.8Mbps
Cloud Service	Available
APP	Secureye Falcon
Power	DC12V±10%
Power Consumption	12W MAX

