

2 MP IP BULLET IR Camera *With* SD Card Support



Features:

- 3.6mm Lens
- 18pcs SMD LED
- 30m IR Range
- H.264/H.265 Compression
- Smart Analytics
- Up to 128G TF card supported



Specification		S-IP-W1-TF
Camera	Sensor+DSP	3516EV200+F23
	Sensor	1/2.9" Progressive scan CMOS
	Min. Illumination	0.01lux(Color), 0lux(IR on)
	Lens	3.6 mm@F2.0: horizontal FOV: 82°, vertical FOV:44°
	Lens Mount	M12
	IR	18pcs SMD LED
	IR Range	30m
	Smart IR	Support
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Day/Night	IR cut filter with auto switch
	Wide Dynamic Range	DWDR
	Digital noise reduction	2D/3D DNR
	Compression	Video Compression
H.264 Codec profile		Base/Main/High profile
H.265 Codec profile		Main profile
Video Bit Rate		11 Kbps~10 Mbps
Image	Max. Image Resolution	1920 × 1080
	Frame Rate	50Hz: 25fps 1080P(1920 × 1080), 25fps 960P(1280 × 960), 25fps 720P(1280 × 720) 60Hz:30fps 1080P(1920 × 1080), 30fps 960P(1280 × 960),30fps 720P(1280 × 720)
	Sub Stream	50Hz:25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	BLC	Support
	HLC	Support
	ROI	Support
Network	Defog	Support
	Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour, IPV6
	Event	Motion Detection, Video Shelter
	Smart Functions	Line Crossing,Area Intrusion,Region Entrance,Region Exiting,Fast Moving.
	System compatibility	Onvif(Profile S), CGI
	Security	User authentication,IP address filtering,Video mask
	Mobile Surveillance	iPhone, iPad,Android,CMS,WEB
General	Communication interface	1 RJ45 10M / 100M Ethernet Port
	TF	Upto 128G TF card supported
	Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F)Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE Supply	PoE (802.3af)
Power Consumption	MAX. 8.5W	
Weather Proof	IP66	