







WIFI BULLET PTZ CAMERA



| | |
|---------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
|  White Balance |  Wide Dynamic Range |
|  Digital Noise Reduction |  PTZ |
|  Masking |  With StarLIGHT technology |

Features

- 2.0 megapixel HD IP camera, maximum resolution 1920*1080
- Support WIFI, support AP mode
- Support up to 128G TF card storage
- 5.1-51mm 10X optical zoom auto focus lens
- Built-in Mic, support voice monitor
- Pan tilt rotation, horizontal:355°&vertical:90°
- Support P2P, view anywhere & anytime
- FTP Support
- Email alert with snapshot on motion detection
- Inbuilt MIC
- Provide android & iOS APP and professional CMS PC client software



Specification

S-IP-WPT-2POE-10X

| | | S-IP-WPT-2POE-10X |
|----------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video | Sensor | 2.0 megapixel 1/2.9" SONY323 low lux CMOS |
| | Video resolution | Main stream: 1920x1080@18fps, 1280x720@25fps Sub stream: 640x352@25fps, 320x176@25fps |
| | Video compression | H.264 |
| | Lens | 5.1-51mm 10X optical zoom auto focus lens |
| | View angle | 96°~26.2° |
| | Night vision | 4pcs array infrared LEDs, night vision distance 60m |
| Audio | Audio compression | G.726/G.711 |
| | Audio code rate | 8Kbps, 16bit |
| | Audio input | Built-in MIC, support voice monitor |
| Alarm | Motion detecting alarm | Can set 4 independent detection region (1-100 sensitivity can be set) |
| | Alarm linkage | Alarm send pictures to the mailbox, Alarm upload pictures and videos to the FTP server, Alarm record pictures and videos to Micro SD card, Alarm mobile phone message push |
| | Alarm recording | Support Micro SD card and PC client linkage alarm recording |
| Network | Wireless | IEEE 802.11 b/g/n |
| | Ethernet | RJ45 Ethernet |
| | Onvif protocol | Support ONVIF 2.4(backward compatible) |
| Storage | Micro SD card | Support up to 128G micro SD card |
| | Recording mode | Alarm record, timing record |
| | Video playback | Support APP, IE browser, remote client play and download the video |
| PTZ | Rotation angle | Horizon: 0~300°, Vertical: 0~60° |
| | Horizontal speed | 12°/S |
| | Vertical speed | 12°/S |
| | Preset | Support 8 preset points |
| General | Power | DC12V 2A or 48V POE |
| | Operating environment | Environment -20℃~+60℃(-4°F~+140), Humidity 10%~90%, non-condensing |
| | Waterproof level | Ip66 |