

24 GE + 2 SFP PoE Switch



SPECIFICATION	S-24GE-2UG-400W
PoE port	24 10/100/1000 port support IEEE802.3af/at
SFP port	Support
PoE port output power	15.4W/30W IEEE802.3af/at
PoE power supply pins	Both 1/2+,3/6- and 4/5+,7/8-
Whole power	<400W
Protocol standard	IEEE 802.3af/IEEE 802.3at
PoE type	End-span
Transmission distance	100 ~ 150m
Network standard	IEEE 802.3, IEEE802.3u,802.3x,802.3af/at
Network Medium	10/100/1000Mbps 5 class and above non shielded twisted pair
Network Signal Distance	<150m
Switch capability	8.8Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port , 100BASE -tx: 14800pps/port 1000BASE-T: 1488095pps/port
MAC Address	MAC address table 16K
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Temperature	-10° ~ 55° C
Input power	AC100-240V 50/60HZ
Weight	3.9kg
Size	440mm*285mm*44mm(L*W*H)

