

# Smart Cloud IP MINI DOME WiFi Camera



**Motion  
Detection**



**PTZ  
Control**



**Audio  
Two Way Audio**



**2.4G WiFi  
Supported**



**Cloud Storage  
Supported**



**Optical Zoom  
4X Optical Zoom**

**Features:**

- Easy installation, plug and play
- View the video anytime and anywhere; support multiple platforms, terminals and networks
- Clear and smooth video, intelligent transmission
- Bank level security control and ensure privacy
- Online firmware upgrade, update function and experience synchronously
- Smart H.264 video compression algorithm, with lower video bit rates and saving more space when recording
- Support Android/iOS system mobile device, remote real-time monitoring
- Support Pan&Tilt(H:355°& V:90°), With preset function, PTZ can be cruised and monitored
- Motion detection, linkage snapshot/video recording, real-time App push notifications
- Infrared night vision lighting (IR distance: 30 meters), 24 hours day and night monitoring, IR-CUT switch
- Support 2.4G WiFi (IEEE802.11b/g/n)
- Support Voice Dialogue, Built-in MIC and 2W High Power Horn
- Support max 512G SD card
- Support Cloud storage, micro SD card storage and cloud box and External SD card slot, easy to install
- Support QR code login

Specification		S-PTZ-D2IP-4X-W
Image Sensor	Image Sensor	1/2.9"color CMOS sensor
	Lens	f:2.8-12mm, 2.0MP
	Visual Angle	H : 51°; V : 29°; D : 62° (Focus 2MP)
	Illumination	0.01Lux
Audio	Input/output	Built-in MIC and speaker
	Compression	AAC
Video	Video Compression	Smart H.264
	Lighting Frequency	Max 30fps
	Display Resolution	1920*1080
	Image Adjustment	Brightness, Contrast, Saturation, Sharpness & Adjustable
	White Balance, BLC	Automatically
	Night Vision	6 Infrared lights(850nm) & 2 White LED, IR distance: 30 meters
Network	Wireless Networks	2.4G WIFI(IEEE802.11b/g/n),external 3DB antenna
	Ethernet	10/100Mbps
	Protocols	TCP/IP, UDP/IP, HTTP, DHCP, RTMP, MUDP
	IP Address	Static IP address & Dynamic IP address
Alarm	Alarm Detection	Motion detection
	Alarm Linkage	Snapshot, audio/video record
	Alarm Notification	Real-time App push notifications
Intelligence	First Generation	Alexa
Interface	Power	DC 12V, Power consumption < 15W
	Buttons	A reset button
	Ethernet Interface	RJ45



[www.secureye.com](http://www.secureye.com)

<b>Others</b>	Pan&Tilt	H:355°& V:90°
	Adjustable Lens	Zoom lens focal length: 2.8-12mm
	LED Instructions	Network signal indicator
	IP Level	IP66
	Video Storage	Micro SD Card (Max 512GB), Cloud box and Cloud storage
<b>Environment</b>	Work Temperature	-20° ~ 55°C (-2°F ~ 131°F)
	Work Humidity	10% ~ 80% (no condensation)
	Storage Temperature	-20°C ~ 60° (-2°F ~ 140°F)
	Storage Humidity	0% ~ 90%(no condensation)
Certificate		RoHS, CE, FCC