

2MP IP Motorized Bullet Camera with True WDR



Features:

- Resolution up to 2MP(1920 × 1080)
- On-board storage up to 128GB
- Support alarm triggering by specified target types (human), Video Shelter
- System compatibility Onvif (Profile S), CGI
- Support Audio Input/ Output
- Support Alarm Input/ Output
- Support TF Card
- Support Smart Analytics Function
- Support Smart SMD Feature

Specification		S-IP-W2-VP-WDRM
Camera	Sensor+DSP	IMX307+NT98566
	Sensor	1/2.8" Progressive scan CMOS Sensor
	Min. Illumination	0.01lux(Color), 0lux(IR on)
	Lens Type & Focal Length	motorized Varifocal lens,2.7~13.5mm
	FOV	horizontal FOV: 100°~40°, vertical FOV:53°~22°,diagonal FOV:115°~47°
	IR	4pcs Array LED
	IR Range	50m
	Smart IR	Support
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Day/Night	IR cut filter with auto switch
	Wide Dynamic Range	DWDR/WDR
	Digital noise reduction	2D/3D DNR
	Video Compression	H.264/H.265/H.264+/H.265+
	Compression Standard	H.264 Codec profile
H.265 Codec profile		Main profile
Video Bit Rate		11 Kbps~8Mbps
Audio Compression		G.711A(-A Model) · G.711U
Audio Bit Rate		64 Kbps(-A Model)
Image	Max. Image Resolution	1920 × 1080
	Frame Rate	50Hz:25fps 1080P(1920 × 1080), 25fps 960P(1280 × 960), 25fps 720P(1280 × 720) 60Hz:30fps 1080P(1920 × 1080), 30fps 960P(1280 × 960), 30fps 720P(1280 × 720)
	Sub Stream	50Hz:25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480), 30fps CIF(352 × 240)
	Third Stream	50Hz:25fps CIF(352 × 288), 60Hz:30fps CIF(352 × 240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	Rotate	Support
	BLC	Support
	HLC	Support
	ROI	Support
	Defog	Support

Network	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour, IPV6
	Event	Motion detection (support alarm triggering by specified target types (human)), Video Shelter
	Smart Functions	Line Crossing Area Intrusion Region Entrance Region Exiting Fast Moving
	System compatibility	Onvif (Profile S), CGI
	Security	User authentication, IP address filtering, Video mask
	WEB	IE, Edge, Chrome, Firefox
	Mobile Surveillance	iPhone, Android
	Interface	Communication interface
On-board storage		up to 128GB
Mic		Support
Reset button		Support
Audio I/O		1/1(-A,-P)
Alarm I/O		1/1
General	Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE	PoE (802.3af)
	Power Consumption	MAX. 10W
	Weather Proof	Ip67
	Vandalproof	Ik10

