

5MP IP BULLET IR Varifocal Camera



Support
H.265
COMPRESSION

Specification		S-IP-W5-VF	
Camera	Sensor+DSP	IMX335+Hi3516EV300	
	Sensor	1/2.8" Progressive scan CMOS Sensor	
	Min. Illumination	0.01lux(Color), 0lux(IR on)	
	Lens	2.8-12mm@F1.4: horizontal FOV: 88°~30°, vertical FOV: 65°~23°	
	Lens Mount	∅ 14	
	IR / IR Range	14milX30pcs SMD LED / 50m	
	Smart IR	Support	
	Shutter Time	Auto/Manual, 1/3~1/10000s	
	Day/Night	IR cut filter with auto switch	
	Wide Dynamic Range	DWDR	
	Digital noise reduction	2D/3D DNR	
	Starlight	Support	
	Compression	Video Compression	H.264/H.265
H.264 Codec profile		Base/Main/High profile	
H.265 Codec profile		Main profile	
Video Bit Rate		11 Kbps~10 Mbps	
Image	Max. Image Resolution	5MP(2592 × 1944)(default 15fps)	
	Frame Rate	50Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536),25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 60Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536),30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)	
		Sub Stream	50Hz:25fps 720P(1280 × 720) 25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps 720P(1280 × 720) 30fps D1(704 × 480),30fps CIF(352 × 240)
		Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	BLC, HLC, ROI, Defog	Support	
	Network	Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPv6(NO FTP)
		Event	Motion Detection, Video Shelter
Smart Functions		Line Crossing,Area Intrusion,Region Entrance,Region Exiting,Fast Moving,Face Detection	
System compatibility		Onvif(Profile S), CGI	
Security		User authentication,IP address filtering,Video mask	
Mobile Surveillance		iPhone, iPad,Android, CMS, WEB	
General	Communication interface	1 RJ45 10M / 100M/ Ethernet Port	
	Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) , Humidity 95% or less (non-condensing)	
	Power Supply	DC12V ± 10%	
	POE Supply	PoE (802.3af)	
	Power Consumption	MAX. 8.5W	
Weather Proof	IP67		

