

2U 9HDD 128Ch 4K H.265 **Intelligent NVR**



Features:

- · H.265/H.264 dual stream decoding, embedded Linux operating system
- · Support synchronous recording, remote monitoring, backup; up to 16CH 1080P video synchronous playback and multichannel backward playback
- Standard ONVIF, SLINK, RTSP protocol
- Support DDNS, EMAIL, UPNP, NTP, P2P • and other functions
- Support IE, Mobile phone (Secureye Starling) APP, IMS monitoring
- Support external alarm; Two-way audio • intercom
- · Support our Smart IPC: Target Count, Electric Fence, Human Detection, Retrograde Detection, Leave Position Detection
- · Support IPC centralized management, including IPC parameter configuration, information export and import, real-time information acquisition and upgrade, etc.
- · Support channel grouping, preview tour
- Support disk grouping quotas and disk group storage modes
- Support double password authentication
- Support network monitoring: network traffic, network delay packet loss test, network packet capture backup
- Support current bandwidth, stream information
- Support Raid 0, 1, 5, 6, 10
- Support IPSAN, NAS



ç	Specif	icati
· · · · ·	JUECH	icali

Main Chinest		
Main Chipset	Hi3536	
Operating System	Embedded Linux	
Bandwidth	640M	
Video Format	H.265	
Video Resolution 4K / Smart Functions Target Count, Electric Fer	5MP / 4MP / 3MP / 2MP	
Smart Functions Target Count, Electric Fer	nce, Human Detection, Retrograde Detection,	
Leave Position Det	ection (need front end IPC supported)	
Record Mode Manual, Schedule,	Motion Detection, Timing, Alarm, Stop	
Playback 1	16Ch 1080P, 4Ch 4K	
Backup Mode U	JSB Device/Network	
Video Input 128Ch Digital (4000X	(3000) + 64Ch Preview + 16Ch Playback	
Opposition 64Ch Digital (4000X) Opposition Video Output Audio Input & Output 1 RCA	3000) + 64Ch Preview + 16Ch Playback	
Video Output	1 HDMI, 1 VGA	
Audio Input & Output 1 RCA	1 RCA in, 1 RCA out, HDMI audio	
Alarm Input & Output	4 in 4 out	
BitHDD9 SATA, EacUE-Sata	9 SATA, Each port supports MAX 10TB HDD	
Š E-Sata	1	
₹ Network Interface 2*RJ45 10M/10	00M/1000M self-adaptive LAN port	
Network Interface 2°RJ45 10M/10 Network Function DDNS, EMAIL, UP	NP, NTP, DHCP, IP Filter, PPPoE, P2P	
Smart Phone	iPhone, Android	
USB 3 USB RS485	Ports(2 USB2.0, 1USB3.0)	
RS485	1	
Power Supply Power Consumption	AC100-240V 200W	
Power Consumption	≤50W(without HDD)	

3:10

