

H.265 8MP Network Dome Camera


Features:

- Resolution up to 8MP(3840X2160@20fps), 5MP(3072X1728@25fps), 4MP(2560X1440@25fps), 3MP(2304X1296@25fps), 2MP(1920X1080@25fps)
- Built-in human detection algorithm, support human detection in complex environments
- Support low bit rate and low latency
- H.265/ H.265+ efficient compression, saving bandwidth and storage space
- Support smart IR, prevent infrared overexposure at night
- ICR infrared filter-type automatic switching for real day and night monitoring
- Support external PoE, TF card slot, audio, alarm
- Support 3D digital noise reduction
- Support automatic electronic shutter function to adapt to different monitoring environments
- Support ONVIF, SLINK protocol

| Specification | | ST-IP-DM-010 |
|----------------------|------------------------|---|
| Basic Parameter | Smart Function | Human detection |
| | Main Chipset | T40XP |
| | Image Sensor | 1/2.7", 8MP progressive scan ultra-low illumination CMOS SC8238 |
| | Effective Pixels | 8MP |
| | Min. Illumination | Color : 0.1Lux@F1.2; B&W : 0Lux@F1.2(IR on) |
| | Lens | 4mm |
| | IR Distance | 20-30M (30-IR light) |
| | Noise Reduction | 3D noise reduction |
| | WDR | DWDR (off/ low / medium / high) |
| | Mirror | Off / horizontal mirroring / vertical mirroring / 180° rotation |
| Human Detection | Image Setting | Brightness / contrast / sharpness / saturation / chroma |
| | Responding Speed | ≤1s |
| | Maximum Detection | 5fps/s (color image) |
| | Detection Area | Support specified area, default full screen |
| | Shielded Area | Support 4 areas setting |
| | Upload Method | Private protocol upload |
| Video & Audio Coding | Trigger Method | Video trigger |
| | Encoding Format | H.265+ / H.265/H.264 |
| | Coding Characteristics | Main stream: 8MP(3840X2160)20fps, 5MP(3072X1728@25fps), 4MP(2560X1440@25fps), 3MP(2304X1296@25fps), 2MP(1920X1080@25fps) Sub stream: D1(720X576), VGA(640X480), Q720P(640X360) |
| | Video Bit Rate | Fixed bit rate, variable bit rate(1280kbps-4Mbps) |
| | Video Type | Composite stream / video stream |
| Network Function | Audio Coding Standard | G.711U/64Kbps |
| | Network Interface | 1*RJ45 10M/100M self-adaptive LAN port |
| | Network Protocol | TCP/IP, UDP, HTTP, DHCP, RTSP, NTP |
| | Interface Protocol | ONVIF |
| Port | Network Interface | RJ45 10M/100M network adaptive |
| | PoE | External PoE |
| | TF Card Slot | Up to 512G, Micro SD (EXT3/EXT4) card local storage |
| | Audio | 1 in 1 out |
| | Alarm | 1 in 1 out |
| General | Operation T/H | - 20°C ~ 55°C / 0%-90% |
| | Weatherproof | IP66 |
| | Power Supply | DC12V / PoE |
| | Power Consumption | <10W (MAX) |

