

16 Port 10/100Mbps 2 Uplink GIGA + 1 SFP POE SWITCH



Features:

- 16*10/100/1000Mbps PoE ports, 2*10/100/1000Mbps uplink port, 1*1000Mbps SFP Slot
- Support IEEE802.3af/at
- Support restrain network storm, VLAN function
- Support Max Transmission distance up to 100m
- All port supported by MDI/MDIX auto flip and self-negotiation
- Built-in power supply
- Maximum power of single PoE port: 30 W
- Whole machine power: 300W
- Adopts store-and-forward architecture
- Support lightning protection 4KV

Specification		S-16GE-2UG-1UF-300W-NB
Power	Power Adapter Voltage	AC 110V-240V
	Consumption	300W
Network Connector	PoE Ethernet Port	1~16 Port : 10/100/1000Mbps
	Ethernet port	Uplink Port : 10/100/1000Mbps
	SFP Port	SFP Port: 1000Mbps
	Transmission Distance	1~16 Port : 100/1000Mbps:0~100m; Uplink Port : 0 ~ 100m SFP: depends on the optical module(20km...100km)
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	Network Standard	IEEE802.3/802.3u, IEEE802.3x, IEEE802.ab
	Switching Capacity	38Gbps
	Packet buffer memory	1Mbits
	Throughput	28.272Mpps
	MAC Table	2K
	Paket Forwarding Rate	10Mbps:14880pps/port 100Mbps:148800pps/port 1000Mbps:1488000pps/port
Power Over Ethernet	PoE Standard	IEEE 802.3af/at
	PoE Power Supply	End-Span(1/2+;3/6-)
	PoE Power	af=15.4W, at=30W
RJ45 port	Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Environmental	LED Indicator	LINK/ACT.100Mbps;PoE Status Indicator; Power indicator; Extender
	Working temperature	0°~55°
	Relative Humidity	20~95%
	Storage temperature	-20°~70°

