

4+2 Port
Long Distance 10/100
POE SWITCH



Specification	S-4FE-2UE-LD
PoE Port	1 to 4 support IEEE802.3af/at (10/100M)
UP Link Port	2 Up Link port (10/100M)
Extend	Can be change to EXTEND, extend network cable up to 250m
PoE Output	15.4W/30W IEEE802.3af/at
PoE Pins	1/2+, 3/6 - 4/5+, 7/8 - total 8 pins
PoE Whole Power	<78W
PoE Connection	IEEE 802.3af/IEEE 8.2.3at
PoE Type	End-span
PoE Transmission Distance	<250m
Network Standard	IEEE 802.3, IEEE 802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX: 5 class and above non shielded twisted pair
Network Signal Distance	<250m
Switch Capacity	1 Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE - T: 14880PPS/Port/100BASE-tx:14800pps/port
MAC Address	1K MAC address table
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging, IEEE802.3x Full-duplex and mode and back pressure for Half-duplex mode
Indicator	Each port with 1 LINK/ACT, 100Mbps, EXTEND switch indicator, PoE status indicator, Power indicator
Working Environment	Working Temperature: -10°C ~ 55°C
Input Power	AC 100-240V 50/60HZ
Whole Power	Max 78W

