

4 Port 10/100Mbps with 2 Uplink Port POE SWITCH



Features:

- 8*10/100Mbps PoE ports, 2*10/100Mbps uplink port
- Support IEEE802.3af/at
- Support restrain network storm, VLAN function
- Support Max Transmission distance up to 250m
- All port supported by MDI/MDIX auto flip and self-negotiation
- Built-in power supply
- Maximum power of single PoE port: 30 W
- Whole machine power: 150W
- Adopts store-and-forward architecture
- Fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall
- Support lightning protection 4KV

| Specification | | S-8FE-2UE-LD-NB |
|---------------------|------------------------|--|
| Power | Power Adapter Voltage | AC 110V-240V |
| | Consumption | 150W |
| Network Connector | PoE Ethernet Port | 1 ~ 8 Port : 10/100Mbps |
| | Ethernet port | Uplink Port : 10/100Mbps |
| | Transmission Distance | 1 ~ 8 Port 100Mbps:0~100m; 10Mbps: 0~250m; Uplink Port : 0 ~ 100m |
| | Transmission Medium | Cat5/5e/6 standard network cable |
| Network Switch | Network Standard | IEEE802.3/802.3u, IEEE802.3x,IEEE802.ab |
| | Switching Capacity | 2.0Gbps |
| | Packet Buffer Memory | 1Mbits |
| | Throughput | 1.488Mpps |
| | MAC Table | 1K |
| | Packet Forwarding rate | 10Mbps:14880pps/port, 100Mbps: 148800pps/port |
| Power Over Ethernet | PoE Standard | IEEE 802.3af/at |
| | PoE Power Supply | 12 45 + ,36 78- , 8 core power supply |
| | PoE Power | af=15.4W, at=30W for each port |
| RJ45 port | Port Function | Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode |
| LED Indicator | LED Indicator | LINK/ACT.100Mbps; PoE Status Indicator; Power indicator; Extender |
| | | |
| Environmental | Working temperature | 0°~55° |
| | Relative Humidity | 20~95% |
| | Storage temperature | -20°~70° |

