

# 3 MP 4G PT Camera



- 4mm Lens**
- Supports SD Card Up to 256GB**
- Two Way Audio**
- Ethernet LAN Port**
- Smart Night Vision Mode**
- Supported (LAN Only)**

**Features:**

- 3MP HD Image, clear and crystal
- 2.5-inch ultra-mini body, plastic material, weatherproof and delicate appearance
- Pan: 0°~260°, Tilt: 0°-90°, support 10 preset positions
- Support FTP, Cloud storage and Local TF card video storage to ensure safe storage of video data
- Support MIC and speaker, two-way audio
- With Infrared and spotlight, support three night vision modes, adjustable to achieve full color at night
- Area motion detection, active defense, when someone appear the alert area, camera will turn on the sound alarm, alarm notification will be pushed on your phone
- Support remote monitoring on mobile phones and PC to check the live situation anytime, anywhere
- IP66 waterproof rating, 4000V lightning protection, anti-surge
- Intelligent lighting control fill light, black and white monitoring, color video
- Humanoid Detection & Humanoid Tracking Feature Available
- Support Onvif & RTSP LAN Only
- Support RTMP

Specification		S-IP-D3-PT4G
Basic Specification	Resolution	3MP
	Sensor	1/3" CMOS Sensor
	Shutter	Shutter adaptation
	Lens	4mm
	Rotation Angle	Pan: 0°~260° 20°/S; Tilt: 90° 10°/S
	Day-Night Mode	Infrared filter
	DNR	3D digital noise reduction
	Dynamic Range	Digital WDR
	IR Distance	IR 20-30m, spotlight 15-20m (depends on environment)
Compression	Video Compression	H.265/H.264
	Video Compression	HD/SD, Rate adaptation
	Audio Coding Format	AAC/G711A
Image	Resolution	Main stream: 2304 *1296, Sub stream: 640x360
	Frame Rate	Max 15fps, frame rate self-adaption
	Image reversal	Support horizontal and vertical reversal
	Privacy Masking	Support MAX 4 Zone
	Back Light Compensation	Support
Network	4G Standard	LTE-TDD/LTE-FDD/TD-SCDMA/WCDM
	4G Frequency Band	LTE-FDD:B1/B3/B5/B8;LTE-TDD:B34/B38/B39/B40/B41; WCDMA:B1/B5/B8
	Ethernet	1*RJ 45 Port 10/100 (Auto adept)
Alarm	Intelligent Alarm	Motion detection
	Alarm Notification	Push alarm notification
Storage	Interface	Micro SD Card (Max 256G)
	Cloud Storage	Support
	Onvif	Support LAN Only
	Working Temperature	-20°C ~ 50°C, Working Humidity:<95%(no condensation)
	Power Adapter	DC 12V1A

