

5MP IP Motorized Dome Camera with True WDR



Features:

- Resolution up to 5MP(2880 x 1620)
- Support alarm triggering by specified target types (human), Video Shelter
- System compatibility Onvif (Profile S), CGI
- Support Audio Input/ Output
- Support Alarm Input/ Output
- Support TF Card up to 128GB
- Support Smart Analytics Function
- Support Smart SMD Feature

Specification		S-IP-D5-VP-WDRM
Camera	Sensor+DSP	SC500AI+NT98566
	Image Sensor	1/2.7" Progressive scan CMOS Sensor
	Min. Illumination	0.006lux(Color), 0lux(IR on)
	Lens Type&Focal Length	Motorized Varifocal lens, 2.8~12mm
	FOV	Horizontal FOV:110°~38°, Vertical FOV:58°~21°, Diagonal FOV: 130°~42°
	IR	4pcs Array LED
	IR Range	50m
	StrobeLight	Support
	Smart IR	Support
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Day/Night	IR cut filter with auto switch
	Wide Dynamic Range	WDR & DWDR
	Digital noise reduction	2D/3D DNR
	Compression Standard	Video Compression
H.264 Codec profile		Base/Main/High profile
H.265 Codec profile		Main profile
Video Bit Rate		11 Kbps~10 Mbps
Triple Streams		Support
Audio Compression		G.711A/G.711U
Audio Bit Rate		64 Kbps
Image	Max. Image Resolution	5MP(2880 x 1620)
	Frame Rate	50Hz:20fps 5MP(2880 × 1620) 25fps 4MP(2560 × 1440) 25fps 1080P(1920 × 1080)
		60Hz:20fps 5MP(2880 × 1620) 30fps 4MP(2560 × 1440) 30fps 1080P(1920 × 1080)
		50Hz:25fps 720P(1280 × 720) 25fps D1(704 × 576),25fps CIF(352 × 288), 15fps MJPEG
	Sub Stream	60Hz:30fps 720P(1280 × 720) 30fps D1(704 × 480),30fps CIF(352 × 240) 15fps MJPEG

	Third Stream	50Hz:25fps CIF(352 × 288) 60Hz:30fps CIF(352 × 240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	BLC	Support
	HLC	Support
	ROI	Support
	Defog	Support
	Rotate	Support
Network	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour
	Event	Motion detection (support alarm triggering by specified target types (human)), Video Shelter
	Smart Functions	Line Crossing,Area Intrusion,Region Entrance,Region Exiting,Fast Moving
	System compatibility	Onvif(Profile S), CGI
	Security	User authentication, IP address filtering, Video mask
	WEB	IE, Chrome, Firefox
	Mobile Surveillance	iPhone, Android devices
Interface	Communication interface	1 RJ45 10M / 100M Ethernet Port
	TF Card Support	Up to 128GB
	Reset button	Support
	Audio I/O	1/1
	Alarm I/O	1/1
General	Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE Supply	PoE (802.3af)
	Power Consumption	MAX. 10W
	Weather Proof	IP67
	Vandalproof	IK10
	Material	Metal

