

2MP Network Full Color Camera With Built-in MIC



Features:

- Resolution up to 2MP(1920 × 1080)
- Image Sensor 1/2.9" Progressive scan CMOS Sensor
- Built in Mic
- 3 Warm Light
- System compatibility Onvif (Profile S), CGI
- Support Smart Analytics
- Support Smart Motion Detection

Specification		S-IP-W1-6M-C-A
Camera	Sensor+DSP	GC2053+NT98561
	Image Sensor	1/2.9" Progressive scan CMOS Sensor
	Min. Illumination	0.008lux(Color), 0lux(IR on)
	Illuminator Number	3 (warm light)
	Illumination Distance	35m(warm light)
	Pan/Tilt/Rotation Range	Pan: 0°~360°, Tilt: 0°~90°, Rotation: 0°~360°
Lens	Focal Length	6mm
	Aperture	F1.6
	FOV	horizontal FOV:55°, vertical FOV:30°, diagonal FOV:63°
	Lens Mount	M12
Compression Standard	Video Compression	H.264/H.265/H.264+/H.265+
	H.264 Codec profile	Base/Main/High profile
	H.265 Codec profile	Main profile
	Video Bit Rate	11 Kbps~8 Mbps
	Audio Compression	G.711A/G.711U
	Audio Bit Rate	64 Kbps
Image	Max. Image Resolution	1920 × 1080
	Main Stream	50Hz:25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 25fps 720P(1280 × 720) 60Hz:30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)
	Sub Stream	50Hz:25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)
	Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
	Shutter Time	Auto/Manual, 1/3~1/10000s
	Day/Night	Auto
	Wide Dynamic Range	DWDR
	Digital noise reduction	2D/3D DNR
	BLC	Support
	HLC	Support

	ROI	Support
	Rotate	Support
Smart Feature	Basic Event	Motion detection (support alarm triggering by specified target types (human)), Video Shelter
	Smart Event	Line Crossing, Area Intrusion, Region Entrance, Region Exiting, Fast Moving
Network	Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour
	System compatibility	Onvif(Profile S), CGI
	Security	User authentication, IP address filtering, Video mask
	User	Up to 10 user
	Web Browsers	Plug-in required live view: IE 10, IE 11 Local service: Chrome 57.0+, Firefox 52.0+
	Mobile Surveillance	iPhone, iPad,Android devices
	Communication interface	1 RJ45 10M / 100M Ethernet Port
	Mic	Support
General	Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F), Humidity 95% or less (non-condensing)
	Power Supply	DC12V ± 10%
	POE	PoE (802.3af)
	Power Consumption	MAX. 8W
	Protection Level	IP67
	Housing	Metal+Plastic

